

Tips for long-term beauty and operation

PROVIA DOOR CLEANING & MAINTENANCE

ProVia doors are built to last and to enhance your home's curb appeal for many years. Basic cleaning and maintenance steps will help keep them operating at peak performance and looking like new. Select your door type below to view cleaning and maintenance tips.

Signet® Oak 460 with Esmond
Decorative Glass and Custom Stain

How to keep your ProVia doors looking beautiful

ENTRY DOOR MAINTENANCE & CLEANING

If you have purchased a fiberglass front door or steel entry door for the first time, you may be wondering what you need to do to keep it looking as beautiful as the day you installed it. Fortunately, ProVia Embarq™, Signet®, and Heritage™ fiberglass doors and Legacy™ steel entry doors are constructed for long-term durability, energy efficiency and beauty. Some basic steel and fiberglass door maintenance will keep them looking great and help keep them operating to their fullest potential. Here are some important steps to take throughout the year.

FINISH

- To clean doors, wash with mild soap and water, rinse with clear water and wipe dry.
- Keep weatherstrip clean of dirt and grit for proper seal. Wash with mild soap and water, rinse with clear water and wipe dry. Apply a light coat of wax and wipe off excess.
- For scuff marks on painted finishes, use mild liquid cleanser, rinse with clear water and wipe dry.
- If finish is accidentally scratched or chipped, clean as recommended above and use touch-up paint supplied or standard wood finish repair crayon.

CAUTION: DO NOT USE paint thinners, lacquer thinner, gasoline, kerosene, or any other harsh chemical to clean surfaces of door or hardware.

HARDWARE

- Much like sterling silver, even the finest brass will react naturally to the elements surrounding it. To maintain, polish with a nonabrasive automotive or furniture wax. By keeping your hardware cleaned and maintained you will be rewarded with a long-lasting finish.
- Tighten screws on lockset and hinges when necessary.
- Lightly oil hinges as needed. Wipe off excess.